

DECORATIVE EFFECT TECHNICAL DATA SHEET

CEMFILLER 0.5 (for walls)

Microcement Classic Effect

DECORATIVE EFFECT DESCRIPTION:	CEMFILLER 0.5 Microcement is a decorative effect that imitates the texture of polished concrete.
APPLICATION:	For interior use.
COLOURING METHOD	Can be tinted with Cameleo pigments.
SUBSTRATE PREPARATION:	As specified in the CEMFILLER Product Technical Data Sheet.
PRODUCT PREPARATION:	As specified in the CEMFILLER Product Technical Data Sheet.
STAGES OF APPLICATION:	
PRODUCTS USED TO CREATE THE EFFECT:	Preparation and application of a Cameleo decorative effect should be carried out by a trained contractor.
1. Primer (optional):	CAMEPRIMER P100 Consumption: up to 0.115 l/m² Application tools: Paint roller, brush Application: Apply one coat of CAMEPRIMER P100 primer to the properly prepared substrate using a paint roller. Drying time: 2 h
2. Undercoat:	CAMEPRIMER P300 Consumption: up to 0.115 kg/m² Application tools: Paint roller, brush Application: Apply one coat of CAMEPRIMER P300 undercoat in the appropriate colour to the properly prepared substrate using a paint roller.



DECORATIVE EFFECT TECHNICAL DATA SHEET

CEMFILLER 0.5 (for walls)

Microcement Classic Effect

EN VERSION 7.0, DATE: 12-01-2026

www.cameleo.pl

	Drying time: 2 h
4. Decorative plaster:	CEMFILLER 0.5 (first coat)
	Consumption: up to 0.65 kg/m ² of dry product at 1 mm layer thickness
	Application tools: Venetian trowel
	Apply the first coat of correctly prepared CEMFILLER 0.5 decorative plaster to the prepared surface using a Venetian trowel.
	Drying time: 12 h (per coat)
5. Decorative plaster:	CEMFILLER 0.5 (second coat)
	Consumption: up to 0.6 kg/m ² of dry product at 1 mm layer thickness
	Application tools: Venetian trowel
	Apply the second coat of correctly prepared CEMFILLER 0.5 decorative plaster over the dry first coat.
	Drying time: 12 h (per coat)
6. Protective varnish:	CAMELAZUR L100
	Consumption: up to 0.115 l/m ² (first coat), 0.06 l/m ² (second coat)
	Application tools: Microfibre paint roller
	Using a microfibre paint roller, apply two coats of correctly prepared Camelazur L100 varnish to the dry CEMFILLER 0.5 decorative plaster surface, taking care to avoid runs.
	Drying time: 4 h (per coat)
EFFECT	At 20°C and 50% air humidity:
DRYING TIME:	Touch dry: 4 h after application of the final coat
	Fully cured: After 14 days
TOOL	Warm soapy water
CLEANING:	



SURFACE CLEANING:	The surface may be washed 14 days after completion of the full application process. Do not use detergents. Clean with soapy water.
APPLICATION CONDITIONS:	Application temperature: +10°C to +30°C. Minimum substrate temperature: +10°C. Maximum substrate temperature: +30°C. Substrate moisture content must not exceed 4%. Maximum air humidity: 75%.
GUIDELINES:	The Decorative Effect Technical Data Sheet describes the decorative effect and the stages of application. It does not guarantee correct execution of the effect. The final appearance of the surface on which the decorative technique is applied depends on the contractor's individual working method and experience. Before starting the decorative effect, a trial application on a sample surface is recommended. For areas exceeding 10 m ² , work in a team of 2-3 people. The effect can be applied by one person if the surface is divided into smaller sections. The recommended area for one person should not exceed 10 m ² . For surfaces more than 3 m high, the use of construction scaffolding is recommended.
WARRANTY:	Product: Cameleo Leśniewicz Grądkowska Spółka Jawna warrants that Cameleo products are of merchantable quality and comply with the standards declared by Cameleo. Cameleo products are covered by warranty provided that they are used in accordance with the instructions in the Product Technical Data Sheets and Decorative Effect Technical Data Sheets. Products are not covered by warranty if they are not used in accordance with the information in the Product Technical Data Sheets and Decorative Effect Technical Data Sheets. Liability under this warranty, if the product proves defective, is limited exclusively to replacement of the product or a refund of its purchase price. This warranty is valid for one year from the date of purchase of the product. Effect: Cameleo Leśniewicz Grądkowska Spółka Jawna warrants that Cameleo effects are of merchantable quality and comply with the standards declared by Cameleo in the Product Technical Data Sheets and Decorative Effect Technical Data Sheets. Cameleo effects are covered by warranty provided that they have been applied by certified individuals or companies trained in professional application at Cameleo's premises or at the premises of a certified representative of Cameleo products in Poland or elsewhere in the world. Liability under this warranty, if the effect proves defective and was applied by a certified Cameleo contractor, is limited exclusively to replacement of the products used to create the effect or a refund of the purchase price of those products. This warranty is valid for 2 years from the date of purchase of the products used to create the effect.
MANUFACTURER:	CAMELEO Leśniewicz Grądkowska Spółka Jawna, ul. Sikorskiego 139, 63-100 Psarskie. Tel. 61-28-35-899

