

DECORATIVE EFFECT TECHNICAL DATA SHEET

CONCRETE EFFECT

Classic Effect



DECORATIVE EFFECT TECHNICAL DATA SHEET

CONCRETE EFFECT

Classic Effect

EN VERSION 7.0, DATE: 12-01-2026

www.cameleo.pl

DECORATIVE EFFECT DESCRIPTION:	CONCRETE EFFECT Classic Effect is a decorative effect that imitates the texture of concrete.	
APPLICATION:	For interior use.	
COLOURING METHOD	Can be tinted with Cameleo pigments.	
SUBSTRATE PREPARATION:	As specified in the CONCRETE EFFECT Classic Effect Product Technical Data Sheet.	
PRODUCT PREPARATION:	As specified in the CONCRETE EFFECT Classic Effect Product Technical Data Sheet.	
	STAGES OF APPLICATION:	
PRODUCTS USED TO CREATE THE EFFECT:	Preparation and application of a Cameleo decorative effect should be carried out by a trained contractor.	
1. Primer (optional):	CAMEPRIMER	P100
	Consumption: up to 0.115 l/m ²	
	Application tools: Paint roller, brush	
	Application: Apply one coat of CAMEPRIMER P100 primer to the properly prepared substrate using a paint roller.	
	Drying time: 2 h	
2. Undercoat:	CAMEPRIMER	P300
	Consumption: up to 0.115 l/m ²	
	Application tools: Paint roller, brush	
	Application: Apply one coat of CAMEPRIMER P300 undercoat in the appropriate colour to the properly prepared substrate using a paint roller.	
	Drying time: 2 h	
3. Decorative plaster:	CONCRETE	EFFECT
	Consumption: up to 1.25 kg/m ²	



Application tools: Venetian trowel, paint roller

Apply one coat of CONCRETE EFFECT Classic Effect plaster to the properly prepared substrate. Work on an area of 3 - 4 m². After applying the plaster, use a paint roller to create the required pattern (lifting the plaster) and leave the entire surface for approximately 20 - 25 min. Then gently smooth the entire surface with a Venetian trowel and leave to dry. Work continuously until the surface is completely covered with CONCRETE EFFECT Classic Effect plaster.

Drying time: 12 h

4. Decorative varnish: CAMELAZUR L100

Consumption: up to 0.115 l/m²

Application tools: Paint roller (microfibre), brush

Apply clear CAMELAZUR L100 varnish to the dry CONCRETE EFFECT CLASSIC EFFECT plaster surface using a microfibre paint roller, taking care not to leave any runs.

Drying time: 4 h

EFFECT
DRYING TIME:

At 20°C and 50% air humidity:

Touch dry: 4 h after application of the final coat

Fully cured: After 7 days

TOOL
CLEANING:

Warm soapy water

SURFACE
CLEANING:

The surface may be washed 14 days after completion of the full application. Do not use detergents. Clean with soap and water.

APPLICATION
CONDITIONS:

Application temperature: +10°C - +30°C. Minimum substrate temperature: +10°C. Maximum substrate temperature: +30°C. Substrate moisture content must not exceed 4%. Maximum air humidity: 75%.

GUIDANCE:

The Decorative Effect Technical Data Sheet describes the decorative effect and its application stages. It does not guarantee correct execution of the effect. The final appearance of the surface on which the decorative technique is applied depends on the contractor's individual working method and experience. Before starting work on the decorative effect, it is advisable to carry it out on a test area.



For surfaces exceeding 10 m², work in a team of 2 - 3 people. The effect can be applied by one person, in which case the surface should be divided into smaller sections. The recommended area for one person should not exceed 10 m². For surfaces more than 3 m high, the use of construction scaffolding is recommended.

WARRANTY:

For the product: Cameleo Leśniewicz Gradowska Spółka Jawna warrants that Cameleo products are of merchantable quality in accordance with the standards declared by Cameleo. Cameleo products are covered by the warranty provided that they are used in accordance with the instructions in the Product Technical Data Sheets and Decorative Effect Technical Data Sheets. Products are not covered by the warranty if they are not used in accordance with the information in the Product Technical Data Sheets and Decorative Effect Technical Data Sheets. Liability under this warranty (if the product proves defective) is limited solely to replacement of the product or a refund of its purchase price. This warranty is valid for one year from the date of purchase of the product.

For the effect: Cameleo Leśniewicz Gradowska Spółka Jawna warrants that Cameleo effects are of merchantable quality in accordance with the standards declared by Cameleo in the Product Technical Data Sheets and Decorative Effect Technical Data Sheets. Cameleo effects are covered by the warranty provided that they have been applied by certified individuals or companies trained in professional application at Cameleo headquarters or by a certified representative of Cameleo products in Poland or elsewhere in the world. Liability under this warranty (if the effect proves defective and has been applied by a certified Cameleo contractor) is limited solely to replacement of the products used to create the effect or a refund of their purchase price. This warranty is valid for 2 years from the date of purchase of the products used to create the effect.

MANUFACTURER:

CAMELEO Leśniewicz Gradowska Spółka Jawna, ul. Sikorskiego 139, 63-100 Psarskie. Tel. 61-28-35-899

