

DECORATIVE EFFECT TECHNICAL DATA SHEET

CONCRETE EFFECT

Smooth Effect

DECORATIVE EFFECT DESCRIPTION:	CONCRETE EFFECT Smooth Effect is a decorative effect that imitates the texture of polished concrete.
APPLICATION:	For interior use.
COLOURING METHOD	Can be tinted with Cameleo pigments.
SUBSTRATE PREPARATION:	As specified in the CONCRETE EFFECT Smooth Effect Product Technical Data Sheet.
PRODUCT PREPARATION:	As specified in the CONCRETE EFFECT Smooth Effect Product Technical Data Sheet.
STAGES OF APPLICATION:	
PRODUCTS USED TO CREATE THE EFFECT:	Preparation and application of a Cameleo decorative effect should be carried out by a trained contractor.
1. Primer (optional):	<p>CAMEPRIMER P100</p> <p>Consumption: up to 0.115 l/m²</p> <p>Application tools: Paint roller, brush</p> <p>Application: Apply one coat of CAMEPRIMER P100 primer to the properly prepared substrate using a paint roller.</p> <p>Drying time: 2 h</p>
2. Undercoat:	<p>CAMEPRIMER P300</p> <p>Consumption: up to 0.115 l/m²</p> <p>Application tools: Paint roller, brush</p> <p>Application: Apply one coat of CAMEPRIMER P300 undercoat in the appropriate colour to the properly prepared substrate using a paint roller.</p>



	Drying time: 2 h
3. Decorative plaster:	<p>CONCRETE EFFECT</p> <p>Consumption: up to 0.8 kg/m²</p> <p>Application tools: Venetian trowel</p> <p>Apply a coat of CONCRETE EFFECT plaster to the properly prepared substrate. Work on an area of 3 - 4 m². After applying the plaster, leave the entire surface for approximately 15 - 20 min. Then gently smooth the entire surface with a Venetian trowel and leave to dry. Work continuously until the surface is completely covered with CONCRETE EFFECT plaster.</p> <p>Drying time: 12 h</p>
4. Decorative varnish:	<p>CAMELAZUR L100</p> <p>Consumption: up to 0.115 l/m²</p> <p>Application tools: Paint roller (microfibre), brush</p> <p>Apply clear CAMELAZUR L100 varnish to the dry CONCRETE EFFECT Smooth Effect plaster surface using a microfibre paint roller, taking care not to leave any runs.</p> <p>Drying time: 4 h</p>
5. Protective wax: (optional)	<p>CAMEWAX TRANSPARENT</p> <p>Consumption: up to 0.01 kg/m²</p> <p>Application tools: Flexible Venetian trowel, microfibre cloth</p> <p>Apply a small amount of clear CAMEWAX wax to the dry surface using a flexible Venetian trowel. After application, leave the entire surface to dry. Then polish the entire surface by hand (with a microfibre cloth) or mechanically (using a car polisher at 3 - 4 thousand revolutions/minute).</p> <p>Drying time: 2 h</p>
EFFECT DRYING TIME:	At 20°C and 50% air humidity:



	Touch dry: 2 h after application of the final coat
	Fully cured: After 7 days
TOOL CLEANING:	Warm soapy water
SURFACE CLEANING:	The surface may be washed 14 days after completion of the full application. Do not use detergents. Clean with soap and water.
APPLICATION CONDITIONS:	Application temperature: +10°C - +30°C. Minimum substrate temperature: +10°C. Maximum substrate temperature: +30°C. Substrate moisture content must not exceed 4%. Maximum air humidity: 75%.
GUIDANCE:	<p>The Decorative Effect Technical Data Sheet describes the decorative effect and its application stages. It does not guarantee correct execution of the effect. The final appearance of the surface on which the decorative technique is applied depends on the contractor's individual working method and experience. Before starting work on the decorative effect, it is advisable to carry it out on a test area.</p> <p>For surfaces exceeding 10 m², work in a team of 2 - 3 people. The effect can be applied by one person, in which case the surface should be divided into smaller sections. The recommended area for one person should not exceed 10 m². For surfaces more than 3 m high, the use of construction scaffolding is recommended.</p>
WARRANTY:	<p>For the product: Cameleo Leśniewicz Grądkowska Spółka Jawna warrants that Cameleo products are of merchantable quality in accordance with the standards declared by Cameleo. Cameleo products are covered by the warranty provided that they are used in accordance with the instructions in the Product Technical Data Sheets and Decorative Effect Technical Data Sheets. Products are not covered by the warranty if they are not used in accordance with the information in the Product Technical Data Sheets and Decorative Effect Technical Data Sheets. Liability under this warranty (if the product proves defective) is limited solely to replacement of the product or a refund of its purchase price. This warranty is valid for one year from the date of purchase of the product.</p> <p>For the effect: Cameleo Leśniewicz Grądkowska Spółka Jawna warrants that Cameleo effects are of merchantable quality in accordance with the standards declared by Cameleo in the Product Technical Data Sheets and Decorative Effect Technical Data Sheets. Cameleo effects are covered by the warranty provided that they have been applied by certified individuals or companies trained in professional application at the premises of Cameleo or a certified representative of Cameleo products in Poland or elsewhere in the world. Liability under this warranty (if the effect proves defective and has been applied by a certified Cameleo contractor) is limited solely to replacement of the products used to create the effect or a refund</p>



of the purchase price of the products used to create the effect. This warranty is valid for 2 years from the date of purchase of the products used to create the effect.

MANUFACTURER: CAMELEO Leśniewicz Grądkowska Spółka Jawna, ul. Sikorskiego 139, 63-100 Psarskie. Tel. 61-28-35-899

