

DECORATIVE EFFECT TECHNICAL SHEET

MANHATTAN DARK/LIGHT SILVER

Spatula Effect

DECORATIVE EFFECT DESCRIPTION:	Manhattan Dark/Light Silver Spatula Effect is a thin-layer decorative floor finish with a pleasant metallic velvet effect.
USE:	Indoors.
TINTING	Can be tinted with Cameleo pigments
SUBSTRATE PREPARATION:	In accordance with the MANHATTAN Product Technical Data Sheet.
PRODUCT PREPARATION:	In accordance with the MANHATTAN Product Technical Data Sheet.
STAGES OF CREATING THE EFFECT:	
PRODUCTS USED TO CREATE THE EFFECT:	The preparation and application of the Cameleo decorative effect should be carried out by a trained applicator.
1. Primer (optional):	CAMEPRIMER P100 Consumption up to: 0.115 l/m² Application tools: Paint roller, brush Application: Apply one coat of CAMEPRIMER P100 primer to the properly prepared substrate using a paint roller. Drying time: 2 h
2. Undercoat:	CAMEPRIMER P3000 Consumption up to: 0.45 kg/m² Application tools: Flexible Venetian trowel Application: Using a Venetian trowel, apply a coat of Cameprimer P3000 epoxy undercoat to the properly prepared substrate, tinted to



the appropriate colour. For Manhattan Light Silver, use undercoat colour 1016D; for Manhattan Dark Silver, use undercoat colour 1016B.

Drying time: 12 h

3. Textured paint: MANHATTAN DARK/LIGHT SILVER + HARDENER M01 (first coat)

Consumption up to: 0.12 l/m²

Application tools: Flexible Venetian trowel

Apply the first coat of MANHATTAN DARK/LIGHT SILVER paint to the properly prepared, dry substrate. Apply the paint with a flexible Venetian trowel. Cover the entire surface evenly and leave to dry.

Drying time: 6 h (per coat)

4. Textured paint: MANHATTAN DARK/LIGHT SILVER + HARDENER M01 (second coat)

Consumption up to: 0.1 l/m²

Application tools: Flexible Venetian trowel

Once the first coat has dried, apply the second coat using the same method as for the first coat. Apply the paint with a flexible Venetian trowel. Cover the entire surface evenly and leave to dry.

Drying time: 6 h (per coat)

5. Protective varnish: CAMELAZUR L300 2K + HARDENER H02

Consumption up to: 0.07 kg/m² (first coat), 0.04 kg/m² (second coat)

Application tools: Paint roller, brush

Using a microfibre paint roller, apply two coats of properly prepared Camelazur L300 2K varnish to the dry MANHATTAN paint surface, taking care not to leave runs.

Drying time: 4 h (per coat)



EFFECT	At 20°C and 50% air humidity:
DRYING TIME:	Touch dry: 4 h after application of the final coat.
	Fully cured: After 14 days
TOOL CLEANING:	Warm soapy water
SURFACE CLEANING:	The surface may be washed 21 days after completion of the full application. Do not use detergents. Clean with soap and water.
TECHNICAL INFORMATION:	Slip resistance DIN 51130:2014-02: R9
APPLICATION CONDITIONS:	Application temperature: +10°C – +30°C. Minimum substrate temperature: +10°C. Maximum substrate temperature: +30°C. Substrate moisture content must not exceed 4%. Maximum air humidity: 75%.
GUIDELINES:	The Decorative Effect Technical Sheet describes the decorative effect and its application stages. It does not guarantee correct execution of the effect. The final appearance of the surface to which the decorative technique is applied depends on the applicator's individual working method and experience. Before creating the decorative effect, a trial application on a sample area is recommended. For areas exceeding 10 m², work in a team of 2 – 3 people. The effect can be applied by one person if the surface is divided into smaller sections. The recommended area for one-person application should not exceed 10 m². For surfaces more than 3 m high, the use of scaffolding is recommended.
WARRANTY:	For the product: Cameleo Leśniewicz Gradowska Spółka Jawna warrants that Cameleo products are of merchantable quality in accordance with the standards declared by Cameleo. Cameleo products are covered by warranty provided they are used in accordance with the instructions in the Product Technical Data Sheets and Decorative Effect Technical Sheets. Products are not covered by warranty if they are not used in accordance with the information in the Product Technical Data Sheets and Decorative Effect Technical Sheets. Liability under this warranty (if the product proves defective) is strictly limited to replacement of the product or refund of its purchase price. This warranty is valid for one year from the purchase of the product. For the effect: Cameleo Leśniewicz Gradowska Spółka Jawna warrants that Cameleo effects are of merchantable quality conforming to its declared standards in the Product Technical Data Sheets and Decorative Effect Technical Sheets. The warranty applies to effects created by certified individuals



or companies trained in professional application at Cameleo's premises or those of a certified Cameleo product representative in Poland or elsewhere in the world. Liability under this warranty (if the effect proves defective and was created by a certified Cameleo applicator) is strictly limited to replacement of the products used to create the effect or refund of their purchase price. This warranty is valid for 2 years from the date of purchase of the products used to create the effect.

MANUFACTURER: CAMELEO Leśniewicz Gradkowska Spółka Jawna, ul. Sikorskiego 139, 63-100 Psarskie. Tel. 61-28-35-899

