

DECORATIVE EFFECT TECHNICAL SHEET

RUST EFFECT METALLIC PAINT SILVER

DECORATIVE EFFECT DESCRIPTION:	RUST EFFECT METALLIC PAINT SILVER is an excellent imitation of rust with metallic elements, ideally suited to modern interiors.
USE:	Indoors
TINTING METHOD	The decorative plaster is available in one colour. The final effect depends on the amount of activator applied.
SUBSTRATE PREPARATION:	In accordance with the RUST EFFECT Product Technical Data Sheet.
PRODUCT PREPARATION:	In accordance with the RUST EFFECT Product Technical Data Sheet.
STAGES OF CREATING THE EFFECT:	
PRODUCTS USED FOR THE EFFECT:	Preparation and application of the Cameleo decorative effect should be carried out by a trained applicator.
1. Primer (optional):	CAMEPRIMER P100 Consumption: up to 0.115 l/m² Application tools: Paint roller, brush Application: Apply one coat of CAMEPRIMER P100 primer to the properly prepared substrate using a paint roller. Drying time: 2 h
2. Undercoat:	CAMEPRIMER P300 (1016B) Consumption: up to 0.115 l/m² Application tools: Paint roller, brush Application: Apply one coat of CAMEPRIMER P300 undercoat in the appropriate colour to the properly prepared substrate using a paint roller.



Drying time: 2 h

3. Metallic paint: METALLIC PAINT SILVER

Consumption: up to 25 - 100 ml/m²

Application tools: Paint roller, brush

Apply a coat of METALLIC PAINT SILVER metallic paint to the properly prepared substrate. Work continuously until the entire surface is covered with METALLIC PAINT SILVER.

Drying time: 6 h

4. Decorative plaster: RUST EFFECT

Consumption: up to 0.4 kg/m² (dry product)

Application tools: Flexible Venetian trowel

Apply a coat of RUST EFFECT plaster to the properly prepared substrate. After applying the plaster, use a flexible Venetian trowel to create the desired pattern. Work continuously until the entire surface is covered with RUST EFFECT plaster.

Drying time: 6 h

5. Activator: RUST ACTIVATOR

Consumption: up to 0.1 l/m²

Application tools: Paint roller (microfibre), brush

After applying RUST EFFECT plaster, wait at least 6 h and apply RUST ACTIVATOR over the entire plaster surface using a paint roller. Then leave to dry.

Drying time: 6 h

6. Decorative varnish: CAMELAZUR L100

Consumption: up to 0.08 l/m²

Application tools: Paint roller (microfibre), brush



Apply two coats of CAMELAZUR L100 clear varnish to the dry surface of RUST EFFECT plaster using a microfibre paint roller, taking care not to leave runs.

Drying time: 4 h (per coat)

**EFFECT
DRYING TIME:**

At 20°C and 50% air humidity:

Touch dry: 4 h after application of the final coat

Fully cured: After 7 days

**TOOL
CLEANING:**

Warm water and soap

**SURFACE
CLEANING:**

The surface may be washed 14 days after completion of the full application. Do not use detergents. Clean with water and soap.

**APPLICATION
CONDITIONS:**

Application temperature: +10°C - +30°C. Minimum substrate temperature: +10°C. Maximum substrate temperature: +30°C. Substrate moisture content must not exceed 4%. Maximum air humidity: 75%.

GUIDANCE:

The Decorative Effect Technical Sheet describes the decorative effect and its application stages. It does not guarantee correct execution of the effect. The final appearance of the surface on which the decorative technique is applied depends on the applicator's individual working method and experience. Before applying the decorative effect, it is recommended to create a sample on a test area. For areas exceeding 10 m², work in a team of 2 - 3 people. The effect can be applied by one person if the surface is divided into smaller sections. The recommended area for one person should not exceed 10 m². For surfaces more than 3 m high, the use of scaffolding is recommended.

WARRANTY:

Product warranty: Cameleo Leśniewicz Grądkowska Spółka Jawna warrants that Cameleo products are of merchantable quality in accordance with the standards declared by Cameleo. Cameleo products are covered by this warranty provided that they are used in accordance with the instructions in the Product Technical Data Sheets and Decorative Effect Technical Sheets. Products are not covered by this warranty if they are not used in accordance with the information in the Product Technical Data Sheets and Decorative Effect Technical Sheets. Liability under this warranty (if the product proves defective) is strictly limited to replacement of the product or a refund of its purchase price. This warranty is valid for one year from the date of purchase of the product.



Effect warranty: Cameleo Leśniewicz Gradkowska Spółka Jawna warrants that Cameleo effects are of merchantable quality in accordance with the standards declared by Cameleo in the Product Technical Data Sheets and Decorative Effect Technical Sheets. Cameleo effects are covered by this warranty provided that they have been applied by certified individuals or companies trained in professional application at Cameleo's premises or by a certified representative of Cameleo products in Poland or elsewhere in the world. Liability under this warranty (if the effect proves defective and was applied by a certified Cameleo contractor) is strictly limited to replacement of the products used to create the effect or a refund of their purchase price. This warranty is valid for 2 years from the date of purchase of the products used to create the effect.

MANUFACTURER: CAMELEO Leśniewicz Gradkowska Spółka Jawna, ul. Sikorskiego 139, 63-100 Psarskie. Tel. 61-28-35-899

