

EFFECT TECHNICAL SHEET

TRAVERTINE MONOCOLOR

Classic Effect

DECORATIVE EFFECT DESCRIPTION:	TRAVERTINE MONOCOLOR Classic Effect is a decorative finish imitating the texture of travertine.
USE:	For indoor use.
TINTING	Can be tinted with Cameleo pigments
SUBSTRATE PREPARATION:	In accordance with the TRAVERTINE Product Technical Data Sheet.
PRODUCT PREPARATION:	In accordance with the TRAVERTINE Product Technical Data Sheet.
STAGES OF APPLICATION:	
PRODUCTS USED TO CREATE THE EFFECT:	The preparation and application of a Cameleo decorative effect should be carried out by a trained applicator.
1. Primer (optional):	CAMEPRIMER P100 Consumption up to: 0.115 l/m² Application tools: Paint roller, brush Application: Using a paint roller, apply one coat of CAMEPRIMER P100 primer to the properly prepared substrate. Drying time: 2 h
2. Undercoat:	CAMEPRIMER P300 Consumption up to: 0.115 l/m² Application tools: Paint roller, brush Application: Using a paint roller, apply one coat of CAMEPRIMER P300 undercoat in the appropriate colour to the properly prepared substrate.



	Drying time: 2 h
3. Decorative plaster:	TRAVERTINE For dry product: 0.8kg/m² Application tools: Venetian trowel, paint roller Apply a coat of TRAVERTINE plaster to the properly prepared substrate. Work on an area of 3 – 4 m². After applying the plaster, use a paint roller to create the desired pattern (lifting the plaster) and leave the entire area for approximately 20 – 25 min. Then gently smooth the whole surface with a Venetian trowel and leave to dry. Work continuously until the entire surface is covered with TRAVERTINE plaster. Drying time: 12 h
4. Decorative varnish:	CAMELAZUR L100 + ADDITIVE MB1005 Consumption up to: 0.115 l/m² Application tools: Paintbrush Use a paintbrush to apply the properly prepared CAMELAZUR L100 varnish with MB1005 additive to the dry TRAVERTINE plaster surface, avoiding runs. Apply the varnish in the direction of the pattern. Drying time: 4 h
EFFECT DRYING TIME:	At 20°C and 50% air humidity: Touch dry: 4 h after application of the last coat Fully hardened: After 7 days
TOOL CLEANING:	Warm soapy water
SURFACE CLEANING:	The surface can be washed 14 days after completion of the full application. Do not use detergents. Clean with soapy water.
APPLICATION CONDITIONS:	Application temperature: +10°C – +30°C. Minimum substrate temperature: +10°C. Maximum substrate temperature: +30°C. Substrate moisture content must not exceed 4%. Maximum air humidity: 75%.



GUIDANCE:

The Effect Technical Sheet describes the decorative effect and the application stages. It does not guarantee correct execution of the effect. The final appearance of the surface on which the decorative technique is applied depends on the applicator's individual working method and experience. Before applying the decorative effect, it is recommended to create it on a test surface.

On surfaces exceeding 10 m², work in a team of 2 – 3 people. The effect can be applied by one person if the surface is divided into smaller sections. The recommended area for one person should not exceed 10 m². For surfaces more than 3 m high, the use of construction scaffolding is recommended.

WARRANTY:

For the product: Cameleo Leśniewicz Gradowska Spółka Jawna warrants that Cameleo products are of merchantable quality in accordance with the standards declared by Cameleo. Cameleo products are covered by this warranty provided that they are used in accordance with the instructions in the Product Technical Data Sheets and Effect Technical Sheets. Products are not covered by this warranty if they are not used in accordance with the information in the Product Technical Data Sheets and Effect Technical Sheets. Liability under this warranty (if the product proves defective) is limited solely to replacement of the product or a refund of its purchase price. This warranty is valid for one year from the date of purchase of the product.

For the effect: Cameleo Leśniewicz Gradowska Spółka Jawna warrants that Cameleo effects are of merchantable quality in accordance with the standards declared by Cameleo in the Product Technical Data Sheets and Effect Technical Sheets. Cameleo effects are covered by this warranty provided that they have been applied by certified individuals or companies trained in professional application at Cameleo's premises or by a certified representative of Cameleo products in Poland or worldwide. Liability under this warranty (if the effect proves defective and was applied by a certified Cameleo applicator) is limited solely to replacement of the products forming the effect or a refund of their purchase price. This warranty is valid for 2 years from the date of purchase of the products forming the effect.

MANUFACTURER:

CAMELEO Leśniewicz Gradowska Spółka Jawna, ul. Sikorskiego 139, 63-100 Psarskie. Tel. 61-28-35-899

