

EFFECT TECHNICAL SHEET

UNI CONCRETE

Classic Effect



EFFECT TECHNICAL SHEET

UNI CONCRETE

Classic Effect

EN VERSION 7.0, DATE: 12-01-2026

www.cameleo.pl

DECORATIVE EFFECT DESCRIPTION: Single-coat decorative plaster imitating the texture of concrete.

USE: For indoor use.

TINTING Can be tinted with Cameleo pigments

SUBSTRATE PREPARATION: In accordance with the UNI CONCRETE Product Technical Data Sheet.

PRODUCT PREPARATION: In accordance with the UNI CONCRETE Product Technical Data Sheet.

STAGES OF APPLICATION:

PRODUCTS USED TO CREATE THE EFFECT: The preparation and application of a Cameleo decorative effect should be carried out by a trained applicator.

1. Primer (optional): CAMEPRIMER P100

Consumption up to: 0.115 l/m²

Application tools: Paint roller, brush

Application: Using a paint roller, apply one coat of CAMEPRIMER P100 primer to the properly prepared substrate.

Drying time: 2 h

2. Undercoat: CAMEPRIMER P300

Consumption up to: 0.115 l/m²

Application tools: Paint roller, brush

Application: Using a paint roller, apply one coat of CAMEPRIMER P300 undercoat in the appropriate colour to the properly prepared substrate.

Drying time: 2 h

3. Decorative plaster: UNI CONCRETE

Consumption up to: 0.85-1 kg/m²



Application tools: Venetian trowel, paint roller

Apply one coat of UNI CONCRETE plaster to the properly prepared substrate. Work in areas of 3–4 m². After applying the plaster, use a paint roller to create the desired pattern (by lifting the plaster) and leave for approximately 20–25 min. Then gently smooth the entire surface with a Venetian trowel and leave to dry. Work continuously until the entire surface is covered with UNI CONCRETE plaster.

Drying time: 12 h

**EFFECT
DRYING TIME:**

At 20°C and 50% air humidity:

Touch dry: After 4 h from application of the final coat

Fully cured: After 7 days

**TOOL
CLEANING:**

Warm soapy water

**SURFACE
CLEANING:**

The surface may be washed 14 days after completion of the full application. Do not use detergents. Clean with soapy water.

**APPLICATION
CONDITIONS:**

Application temperature: +10°C – +30°C. Minimum substrate temperature: +10°C. Maximum substrate temperature: +30°C. Substrate moisture content must not exceed 4%. Maximum air humidity: 75%.

GUIDANCE:

The Effect Technical Sheet describes the decorative effect and its application stages. It does not guarantee that the effect will be executed correctly. The final appearance of the surface on which the decorative technique is applied depends on the applicator's individual working method and experience. Before creating the decorative effect, it is recommended to apply it to a test area.

On surfaces exceeding 10 m², work in a team of 2–3 people. The effect can be created by one person by dividing the surface into smaller sections. The recommended area for one person should not exceed 10 m². For surfaces higher than 3 m, the use of construction scaffolding is recommended.

WARRANTY:

For the product: Cameleo Leśniewicz Grądkowska Spółka Jawna warrants that Cameleo products are of merchantable quality in accordance with the standards declared by Cameleo. Cameleo products are covered by the warranty provided that they are used in accordance with the instructions in the Product Technical Data Sheets and Effect Technical Sheets. Products are not covered by the warranty if they are not used in accordance with the information in the Product Technical Data Sheets and



EFFECT TECHNICAL SHEET

UNI CONCRETE

Classic Effect

EN VERSION 7.0, DATE: 12-01-2026

www.cameleo.pl

Effect Technical Sheets. Liability under this warranty (if the product proves defective) is limited solely to replacement of the product or a refund of its purchase price. This warranty is valid for one year from the date of purchase of the product.

For the effect: Cameleo Leśniewicz Gradkowska Spółka Jawna warrants that Cameleo effects are of merchantable quality in accordance with the standards declared by Cameleo in the Product Technical Data Sheets and Effect Technical Sheets. Cameleo effects are covered by the warranty provided that they have been created by certified individuals or companies trained in professional application at Cameleo's premises or by a certified representative of Cameleo products in Poland or elsewhere in the world. Liability under this warranty (if the effect proves defective and was created by a certified Cameleo applicator) is limited solely to replacement of the products used to create the effect or a refund of their purchase price. This warranty is valid for 2 years from the date of purchase of the products used to create the effect.

MANUFACTURER: CAMELEO Leśniewicz Gradkowska Spółka Jawna, ul. Sikorskiego 139, 63-100 Psarskie. Tel. 61-28-35-899



EFFECT TECHNICAL SHEET

UNI CONCRETE

Classic Effect

EN VERSION 7.0, DATE: 12-01-2026

www.cameleo.pl