

EFFECT TECHNICAL DATA SHEET

VENETIAN STUCCO

Classic Effect

DECORATIVE EFFECT DESCRIPTION:	VENETIAN STUCCO Classic Effect is a decorative coating used to recreate traditional decorative techniques.
USE:	Indoors
TINTING METHOD	Can be tinted with Cameleo pigments
SUBSTRATE PREPARATION:	In accordance with the VENETIAN STUCCO Product Technical Data Sheet.
PRODUCT PREPARATION:	In accordance with the VENETIAN STUCCO Product Technical Data Sheet.
STAGES OF APPLICATION:	
PRODUCTS USED IN THE FINISH:	The Cameleo decorative finish should be prepared and applied by a trained applicator.
1. Primer:	CAMEPRIMER P100 Consumption up to: 0.115 l/m² Application tools: Paint roller, brush Application: Apply one coat of CAMEPRIMER P100 primer to a suitably prepared substrate using a paint roller. Drying time: 2 h
2. Textured paint:	VENETIAN STUCCO (first coat) Consumption up to: 0.25 kg/m² Application tools: Venetian trowel Application: Using a Venetian trowel, apply a coat of VENETIAN STUCCO textured paint to a suitably prepared substrate, ensuring that



no ridges form. Work continuously until the entire surface is covered with VENETIAN STUCCO textured paint. Leave to dry.

Drying time: 6 h

3. Textured paint: VENETIAN STUCCO (second coat)

Consumption up to: 0.15 kg/m²

Application tools: Venetian trowel

Application: Using the Venetian trowelling technique (small, short strokes), cover the entire first coat of textured paint, creating a subtle pattern. Work in this way over the whole surface. Leave to dry.

Drying time: 4 h

4. Textured paint: VENETIAN STUCCO (third coat)

Consumption up to: 0.1 kg/m²

Application tools: Venetian trowel

Application: Using the Venetian trowelling technique (small, short strokes), cover the entire second coat of textured paint, creating a subtle pattern while gently burnishing the VENETIAN STUCCO surface with the clean edge of the Venetian trowel. Leave to dry.

Drying time: 2 h

5. Decorative wax: CAMEWAX

Consumption up to: 0.04 kg/m²

Application tools: Venetian trowel

Application: Apply a small amount of CAMEWAX to the dry VENETIAN STUCCO textured paint surface using a Venetian trowel. Gently smooth the entire surface after applying the wax. After 10 - 15 min., gently polish the waxed surface with the edge of the Venetian trowel or a polishing machine, then leave to dry. Repeat the procedure in rooms particularly prone to soiling.

Drying time: 4 h



FINISH	At 20°C and 50% air humidity:
DRYING TIME:	Touch dry: 4 h after application of the final coat
	Fully cured: After 7 days
TOOL CLEANING:	Warm soapy water
SURFACE CLEANING:	The surface may be washed 7 days after completion of the full application. Do not use detergents. Clean with soapy water.
APPLICATION CONDITIONS:	Application temperature: +10°C - +30°C. Minimum substrate temperature: +10°C. Maximum substrate temperature: +30°C. Substrate moisture content must not exceed 4%. Maximum air humidity: 75%.
GUIDANCE:	The Effect Technical Data Sheet describes the decorative finish and its application stages. It does not guarantee correct execution of the finish. The final appearance of the surface on which the decorative technique is applied depends on the applicator's individual working method and experience. It is advisable to carry out a trial application before applying the decorative finish. For areas exceeding 10 m², work in a team of 2 - 3 people. The finish can be applied by one person, in which case the surface should be divided into smaller sections. The recommended area for one person should not exceed 10 m². For surfaces over 3 m high, the use of construction scaffolding is recommended.
WARRANTY:	For the product: Cameleo Leśniewicz Gradkowska Spółka Jawna warrants that Cameleo products are of merchantable quality in accordance with the standards declared by Cameleo. Cameleo products are covered by the warranty provided that they are used in accordance with the instructions in the Product Technical Data Sheets and Effect Technical Data Sheets. Products are not covered by the warranty if they are not used in accordance with the information in the Product Technical Data Sheets and Effect Technical Data Sheets. Liability under this warranty (if the product proves defective) is strictly limited to replacement of the product or a refund of its purchase price. This warranty is valid for one year from the date of purchase of the product. For the finish: Cameleo Leśniewicz Gradkowska Spółka Jawna warrants that Cameleo finishes are of merchantable quality in accordance with the standards declared by Cameleo in the Product Technical Data Sheets and Effect Technical Data Sheets. Cameleo finishes are covered by the warranty provided that they have been applied by certified individuals or companies trained in professional application at Cameleo's premises or by a certified representative of Cameleo products in Poland or worldwide. Liability under this warranty (if the finish proves defective and



was applied by a certified Cameleo applicator) is strictly limited to replacement of the products forming part of the finish or a refund of their purchase price. This warranty is valid for 2 years from the date of purchase of the products forming part of the finish.

MANUFACTURER: CAMELEO Leśniewicz Grądkowska Spółka Jawna, ul. Sikorskiego 139, 63-100 Psarskie. Tel. 61-28-35-899

