

PRODUCT TECHNICAL DATA SHEET

CONCRETE EFFECT

Decorative plaster



DESCRIPTION:	Single-coat decorative plaster that imitates the texture of concrete.
COLOUR:	Grey base
COLOURING METHOD	Can be tinted with Cameleo pigments.
SUBSTRATE PREPARATION:	<p>Unpainted substrates:</p> <p>Unpainted substrates include:</p> <ul style="list-style-type: none"> - Cement and cement-lime plasters; - Concrete substrates; - Substrates reinforced with fibreglass mesh; - Gypsum skim coats; - Plasterboard. <p>Fresh cement and cement-lime plasters and new concrete substrates must be allowed to cure for at least 30 days; substrate moisture content must not exceed 4%.</p> <p>Substrates reinforced with fibreglass mesh must be allowed to cure for at least 3 days.</p> <p>Gypsum skim coats should be completely dry.</p> <p>Plasterboard joints must be carefully filled.</p> <p>Remove dirt, dust and greasy stains from all the substrates listed above. Level any uneven areas and fill cracks, then apply one coat of CAMEPRIMER P100 primer to the entire surface.</p> <p>Painted substrates:</p> <p>Painted substrates must be sound and have good adhesion. Remove dirt, dust, greasy stains and adhesive residues. Abrade the entire surface with 120-150 grit sandpaper.</p> <p>Level any uneven areas and fill cracks, then apply one coat of CAMEPRIMER P300 undercoat to the entire surface.</p>
PRODUCT PREPARATION:	<p>Pour the contents of the container into the appropriate amount of water (33-35% H₂O per 1 kg). Mix thoroughly using a mechanical mixer. Leave the prepared plaster for approximately 15 min., then mix again immediately before use. When tinting the compound, disperse the pigment in the mixing water, then add the contents of the container and mix thoroughly using a mechanical mixer. Leave the prepared plaster for approximately 15 min., then mix again immediately before use. When working on areas larger than the coverage of a single container, combine and mix the contents of the individual containers in one larger container.</p>
APPLICATION:	Venetian trowel. Single-coat plaster.



TECHNICAL INFORMATION:	<p>Thinner - Water</p> <p>Specific gravity - 1.6 g/ml (water content 33%)</p> <p>Consumption: up to 0.8 kg/m² (dry product)</p> <p>Practical consumption - Consumption depends on many factors, such as substrate porosity and roughness, and material losses during application.</p> <p>pH - 10.5-11.0</p>
RECOMMENDED PRIMERS:	CAMEPRIMER P100, CAMEPRIMER P300
TOOL CLEANING:	Warm soapy water.
SURFACE CLEANING AND CARE:	The surface may be washed 7 days after completion of the full application. Do not use detergents. Clean with soap and water.
PRODUCT DRYING TIME:	<p>At 20°C and 50% air humidity:</p> <p>Touch dry - 2 hours after application.</p> <p>Cured - 7 days after application.</p>
APPLICATION CONDITIONS:	<p>Application temperature: +10°C - +30°C. Minimum substrate temperature: +10°C.</p> <p>Maximum substrate temperature: +30°C. Substrate moisture content must not exceed 4%. Maximum air humidity: 75%.</p>
STORAGE AND TRANSPORT:	<p>Store in a tightly closed container at +5°C - +25°C. The product is sensitive to frost.</p> <p>Protect from sunlight. Shelf life: 12 months from the date of manufacture in the original sealed container (date of manufacture on the container).</p>
PACKAGING:	2 kg, 8 kg, 16 kg
SAFETY INSTRUCTIONS:	All product safety instructions are available in the Safety Data Sheet for the chemical substance (mixture).
APPROVALS/STANDARDS:	PN-EN 15824:2010
VOC	<p>VOC: 1.4 g/l</p> <p>VOC category: A/I</p> <p>VOC limit: 200 g/l</p>
NOTES:	Mix the product thoroughly using a mechanical mixer before use. When working on areas larger than the coverage of a single container, combine and mix the contents of the individual containers in one larger container.



The colours shown in the catalogue may differ from the actual colours on the wall. Colours depend on the application method, texture, gloss, lighting, sunlight and the types and intensity of other colours in the surroundings. Storage, transport and application conditions, as well as the final result, are beyond our control and therefore cannot constitute a warranty in the legal sense. Statutory provisions and any third-party rights must be observed in all cases.

WARRANTY:

Cameleo Leśniewicz Grądkowska Spółka Jawna warrants that Cameleo products are of merchantable quality in accordance with the standards declared by Cameleo. Cameleo products are covered by the warranty provided that they are used in accordance with the instructions in the Product Technical Data Sheets and Decorative Effect Technical Data Sheets. Products are not covered by the warranty if they are not used in accordance with the information in the Product Technical Data Sheets and Decorative Effect Technical Data Sheets. Liability under this warranty (if the product proves defective) is limited solely to replacement of the product or a refund of its purchase price. This warranty is valid for one year from the date of purchase of the product.

MANUFACTURER:

CAMELEO Leśniewicz Grądkowska Spółka Jawna, ul. Sikorskiego 139, 63-100 Psarskie. Tel. 61-28-35-899

