

PRODUCT TECHNICAL DATA SHEET

MANHATTAN (for floors)

Textured paint

DESCRIPTION:	Textured paint with a unique, pleasant velvet effect.
COLOUR:	The paint is available in two bases: MANHATTAN LIGHT SILVER MANHATTAN DARK SILVER
TINTING	Can be tinted with Cameleo pigments
SUBSTRATE PREPARATION:	Before applying the Cameleo decorative effect, prepare the substrate surface properly. – concrete substrates Allow concrete substrates to cure for at least 30 days; their moisture content must not exceed 4%. The concrete substrate grade must be at least C20/25 (B25). Remove all contaminants and dirt mechanically. Apply a coat of CAMEPRIMER P3000 to the prepared substrate.
PRODUCT PREPARATION:	Mix the product by hand; do not mix mechanically! Before use, add 5% HARDENER M01 (80 ml/1.6 L). Then add Cameleo pigment and mix thoroughly again to obtain a uniform paint colour. When working on areas larger than the coverage of a single container, combine and mix the contents of the individual containers in one larger container.
APPLICATION:	Flexible Venetian trowel
TECHNICAL INFORMATION:	Thinner - Water Specific gravity - 1.12 g/ml Consumption up to - 0.22 l/m ² Practical consumption - Consumption depends on many factors, including substrate porosity and roughness, and material losses during application. pH - Approx. 8.7
RECOMMENDED PRIMERS	CAMEPRIMER P100, CAMEPRIMER P3000
TOOL CLEANING:	Warm soapy water.



SURFACE CLEANING AND CARE	The surface may be washed 7 days after completion of the full application. Do not use detergents. Clean with soap and water.
PRODUCT DRYING TIME:	At 20°C and 50% air humidity: Touch dry - 6 hours after application. Cured - 7 days after application
APPLICATION CONDITIONS:	Application temperature: +10°C – +30°C. Minimum substrate temperature: +10°C. Maximum substrate temperature: +30°C. Substrate moisture content must not exceed 4%. Maximum air humidity: 75%.
STORAGE AND TRANSPORT:	Store in a tightly closed container at +5°C – +25°C. The product is sensitive to frost. Protect from sunlight. Shelf life: 12 months from the date of manufacture in the original sealed container (manufacturing date on the packaging).
PACKAGING:	1.6 l, 9.6 l
SAFETY INFORMATION:	All product safety information is available in the Safety Data Sheet for the chemical substance (mixture).
APPROVALS/ STANDARDS:	PN-EN 1062-1:2005 PN-C-81913:1998
VOC	VOC: 1.8 g/l VOC category: A/I VOC limit: 200 g/l
NOTES:	The product must be thoroughly mixed by hand before use. When working on areas larger than the coverage of a single container, combine and mix the contents of the individual containers in one larger container. The colours shown in the catalogue may differ from the actual colours on the wall. Colours depend on the application method, texture, gloss, lighting, sunlight and the types and intensity of other colours in the surroundings. Storage, transport and application conditions, as well as the final effect, are beyond our control and therefore cannot constitute a guarantee in the legal sense. Statutory provisions and any third-party rights must be observed in all cases.
WARRANTY:	Cameleo Leśniewicz Gradowska Spółka Jawna warrants that Cameleo products are of merchantable quality in accordance with the standards declared by Cameleo. Cameleo products are covered by warranty provided they are used in accordance with the instructions in the Product Technical Data Sheets and Decorative Effect Technical Sheets. Products are not covered by warranty if they are not



used in accordance with the information in the Product Technical Data Sheets and Decorative Effect Technical Sheets. Liability under this warranty (if the product proves defective) is strictly limited to replacement of the product or refund of its purchase price. This warranty is valid for one year from the purchase of the product.

MANUFACTURER: CAMELEO Leśniewicz Gradowska Spółka Jawna, ul. Sikorskiego 139, 63-100 Psarskie. Tel. 61-28-35-899

