

PRODUCT TECHNICAL DATA SHEET

TRAVERTINE

Decorative plaster



DESCRIPTION:	Single-coat decorative plaster imitating the texture of travertine.
COLOUR:	Cream base
TINTING	Can be tinted with Cameleo pigments
SUBSTRATE PREPARATION:	Unpainted substrates: Unpainted substrates include: – cement and cement-lime plasters, – concrete substrates, – substrates reinforced with fibreglass mesh, – gypsum skim coats, – plasterboard. Fresh cement and cement-lime plasters and new concrete substrates must be allowed to cure for at least 30 days; the substrate moisture content must not exceed 4%. Substrates reinforced with fibreglass mesh must be left to cure for at least 3 days. Gypsum skim coats must be completely dry. Plasterboard joints must be carefully filled. Remove dirt, dust and grease stains from all the above substrates. Level uneven areas and fill cracks, then prime the entire surface with one coat of CAMEPRIMER P100. Painted substrates: Painted substrates must be sound and have good adhesion. Remove dirt, dust, grease stains and adhesive residues from the surface. Sand the entire surface to a matt finish with 120–150 grit sandpaper. Level uneven areas and fill cracks, then prime the entire surface with one coat of CAMEPRIMER P300 undercoat.
PRODUCT PREPARATION:	Pour the contents of the pack into the appropriate amount of water (33-35% H₂O per 1 kg). Mix everything thoroughly mechanically. Leave the prepared mixture to stand for approximately 15 min., then stir the plaster again immediately before use. When tinting the mixture, disperse the pigment in the mixing water, then add the contents of the pack and mix everything thoroughly mechanically. Leave the prepared mixture to stand for approximately 15 min., then stir the plaster again immediately before use. When working on surfaces larger than the coverage of a single pack, the contents of the individual packs must be mixed together in one larger container.
APPLICATION:	Venetian trowel. Single-coat plaster.



TECHNICAL INFORMATION:	Thinner - Water Specific gravity - 1.56 g/ml (water content 33%) Consumption up to - Dry product: 1.25 kg/m² Practical consumption - Consumption depends on many factors, such as substrate porosity and roughness and material losses during application. pH - Approx. 12.4 (water content 33%)
RECOMMENDED PRIMERS	CAMEPRIMER P100, CAMEPRIMER P300
TOOL CLEANING:	Warm soapy water.
SURFACE CLEANING AND CARE	The surface can be washed 7 days after completion of the full application. Do not use detergents. Clean with soapy water.
PRODUCT DRYING TIME:	At 20°C and 50% air humidity: Touch dry - 2 hours after application. Hardened - 7 days after application
APPLICATION CONDITIONS:	Application temperature: +10°C – +30°C. Minimum substrate temperature: +10°C. Maximum substrate temperature: +30°C. Substrate moisture content must not exceed 4%. Maximum air humidity: 75%
STORAGE AND TRANSPORT:	Store in tightly closed packaging at +5°C – +25°C. The product is sensitive to frost. Protect from sunlight. Shelf life: 12 months from the date of manufacture in the original sealed packaging (date of manufacture shown on the packaging).
PACK SIZES:	2 kg, 8 kg, 16 kg
SAFETY INFORMATION:	All product safety information is available in the Safety Data Sheet for the chemical substance (mixture).
APPROVALS/STANDARDS:	PN-EN 15824:2010
VOC	VOC: 1.0 g/l VOC category: A/I VOC limit: 200 g/l
NOTES:	Mix the product thoroughly by hand before use. When working on surfaces larger than the coverage of a single pack, the contents of the individual packs must be mixed together in one larger container.



The colours shown in the catalogue may differ from the actual colours on the wall. Colours depend on the application method, texture, gloss, lighting, sunlight and the types and intensity of other colours in the surroundings. Storage, transport and application conditions, as well as the final effect, are beyond our control and therefore cannot constitute a guarantee in the legal sense. In all cases, statutory provisions and any third-party rights must be respected.

WARRANTY:

Cameleo Leśniewicz Grądkowska Spółka Jawna warrants that Cameleo products are of merchantable quality in accordance with the standards declared by Cameleo. Cameleo products are covered by this warranty provided that they are used in accordance with the instructions in the Product Technical Data Sheets and Decorative Effect Technical Sheets. Products are not covered by this warranty if they are not used in accordance with the information in the Product Technical Data Sheets and Decorative Effect Technical Sheets. Liability under this warranty (if the product proves defective) is limited solely to replacement of the product or a refund of its purchase price. This warranty is valid for one year from the date of purchase of the product.

MANUFACTURER:

CAMELEO Leśniewicz Grądkowska Spółka Jawna, ul. Sikorskiego 139, 63-100 Psarskie. Tel. 61-28-35-899

