PRODUCT TECHNICAL DATA SHEET

UNI CONCRETE

Decorative plaster

DESCRIPTION:	Single-coat decorative plaster imitating the texture of concrete.
COLOUR:	Grey base
TINTING	Can be tinted with Cameleo pigments
SUBSTRATE PREPARATION:	Unpainted substrates: Unpainted substrates include: – cement and cement-lime plasters, – concrete substrates, – substrates reinforced with fibreglass mesh, – gypsum skim coats, – plasterboard. Fresh cement and cement-lime plasters and new concrete substrates must be allowed to cure for at least 30 days, and the substrate moisture content must not exceed 4%. Substrates reinforced with fibreglass mesh must be allowed to cure for at least 3 days. Gypsum skim coats must be completely dry. Plasterboard joints must be carefully filled. Remove dirt, dust and grease stains from all the substrates listed above. Level any uneven areas and fill cracks, then prime the entire surface with one coat of CAMEPRIMER P100 primer. Painted substrates: Painted substrates must be sound and provide good adhesion. Remove dirt, dust, grease stains and adhesive residues. Sand the entire surface to a matt finish using 120–150 grit sandpaper. Level any uneven areas and fill cracks, then prime the entire surface with one coat of CAMEPRIMER P300 undercoat.
PRODUCT PREPARATION:	Ready-to-use product. Mix thoroughly mechanically. When working on areas larger than the coverage of a single pack, combine the contents of the individual packs in one larger container.
APPLICATION:	Venetian trowel. Single-coat plaster.
TECHNICAL INFORMATION:	Thinner - Water Specific gravity - 1.4 g/cm³ Consumption up to - 0.85-1 kg/m² Practical consumption - Consumption depends on many factors, such as substrate porosity and roughness, and material losses during application. pH - Approx. 8,05 +/-10%

RECOMMENDED PRIMERS	CAMEPRIMER P100, CAMEPRIMER P300
TOOL CLEANING:	Warm soapy water.
SURFACE CLEANING AND CARE	The surface may be washed 7 days after completion of the full application. Do not use detergents. Clean with soapy water.
PRODUCT DRYING TIME:	At 20°C and 50% air humidity: Touch dry - 12 hours after application. Cured - 7 days after application
APPLICATION CONDITIONS:	Application temperature: +10°C – +30°C. Minimum substrate temperature: +10°C. Maximum substrate temperature: +30°C. Substrate moisture content must not exceed 4%. Maximum air humidity: 75%
STORAGE AND TRANSPORT:	Store in tightly closed packaging at +5°C – +25°C. The product is frost-sensitive. Protect from sunlight. Shelf life: 12 months from the production date in the original sealed packaging (production date on the packaging).
PACKAGING:	8 kg, 16 kg
SAFETY GUIDANCE:	All product safety information is available in the Safety Data Sheet for the chemical substance (mixture).
CERTIFICATES/ STANDARDS:	PN-EN 15824:2017
THERMAL CONDUCTIVITY:	λ10,dry,mat 0,61 W/(m·K) (tabulated value, PN-EN 1745, Table A12 for P = 50% and density ≤ 1600 kg/m^3)
REACTION TO FIRE:	Reaction-to-fire class in accordance with: COMMISSION DELEGATED REGULATION (EU) 2017/1228 of 20 March 2017: External renders and internal plasters based on organic binders covered by harmonised standard EN 15824 / Class B-s2, d0
Load at failure, N Adhesion, N/mm^2 Failure type	Required value ≥ 0,3 / Mean value 1,3 +/- 0,5

BIOCIDAL PROTECTION	Keep out of reach of children. Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.
NOTES:	Mix the product thoroughly mechanically before use. When working on areas larger than the coverage of a single pack, combine the contents of the individual packs in one larger container. Colours shown in the catalogue may differ from the actual colours on the wall. Colours depend on the application method, texture, gloss, lighting, sunlight and the types and intensity of other colours in the surroundings. Storage, transport and application conditions, as well as the final result, are beyond our control and therefore cannot constitute a guarantee in the legal sense. Statutory provisions and any third-party rights must be observed in all cases.
WARRANTY:	Cameleo Leśniewicz Gradkowska Spółka Jawna warrants that Cameleo products are of merchantable quality in accordance with the standards declared by Cameleo. Cameleo products are covered by the warranty provided that they are used in accordance with the instructions in the Product Technical Data Sheets and Decorative Effect Technical Sheets. Products are not covered by the warranty if they are not used in accordance with the information in the Product Technical Data Sheets and Decorative Effect Technical Sheets. Liability under this warranty (if the product proves defective) is limited solely to replacement of the product or a refund of its purchase price. This warranty is valid for one year from the date of purchase of the product.
MANUFACTURER:	CAMELEO Leśniewicz Gradkowska Spółka Jawna, ul. Sikorskiego 139, 63-100 Psarskie. Tel. 61-28-35-899