

PRODUCT TECHNICAL DATA SHEET

VENETIAN STUCCO

Textured paint



DESCRIPTION:	Textured paint that creates the appearance of polished marble. It forms a smooth surface that is pleasant to the touch.
COLOUR:	White base
TINTING METHOD	Can be tinted with Cameleo pigments
SUBSTRATE PREPARATION:	Unpainted substrates: Unpainted substrates include: - cement and cement-lime plasters, - concrete substrates, - substrates reinforced with fibreglass mesh, - gypsum skim coats, - plasterboard. Fresh cement and cement-lime plasters and new concrete substrates must be allowed to cure for at least 30 days; substrate moisture content must not exceed 4%. Substrates reinforced with fibreglass mesh must be allowed to cure for at least 3 days. Gypsum skim coats must be completely dry. Plasterboard joints must be carefully filled. Remove dirt, dust and grease from all the above substrates. Level uneven areas and fill cracks, then prime the entire surface with one coat of CAMEPRIMER P100. Painted substrates: Painted substrates must be sound and have good adhesion. Remove dirt, dust, grease and adhesive residues. Sand the entire surface with 120-150 grit sandpaper to produce a matt finish. Level uneven areas and fill cracks, then prime the entire surface with one coat of CAMEPRIMER P300 undercoat.
PRODUCT PREPARATION:	Mix the product by hand or mechanically. When working on areas larger than the coverage of a single pack, combine and mix the contents of individual packs in one larger container.
APPLICATION:	Venetian trowel
TECHNICAL INFORMATION:	Thinner - water Specific gravity - 1.68 g/ml Consumption up to 0.5 kg/m² Practical consumption - Consumption depends on many factors, such as substrate porosity and roughness and material losses during application. pH - Approx. 8.7



RECOMMENDED PRIMERS	CAMEPRIMER P100
TOOL CLEANING:	Warm soapy water.
SURFACE CLEANING AND CARE	The surface may be washed 7 days after completion of the full application. Do not use detergents. Clean with soapy water.
PRODUCT DRYING TIME:	At 20°C and 50% air humidity: Touch dry - 4 hours after application. Cured - 7 days after application
APPLICATION CONDITIONS:	Application temperature: +10°C - +30°C. Minimum substrate temperature: +10°C. Maximum substrate temperature: +30°C. Substrate moisture content must not exceed 4%. Maximum air humidity: 75%.
STORAGE AND TRANSPORT:	Store in a tightly closed container at +5°C - +25°C. The product is sensitive to frost. Protect from sunlight. Shelf life: 12 months from the date of manufacture in the original sealed container (manufacturing date on the packaging).
PACK SIZES:	1 kg, 3 kg, 12 kg, 24 kg
SAFETY INSTRUCTIONS:	All product safety instructions are available in the Safety Data Sheet for the chemical substance (mixture).
VOC	VOC: 16.3 g/l VOC category: A/l VOC limit: 200 g/l
NOTES:	Mix the product thoroughly by hand or mechanically before use. When working on areas larger than the coverage of a single pack, combine and mix the contents of individual packs in one larger container. The colours shown in the catalogue may differ from the actual colours on the wall. Colours depend on the application method, texture, gloss, lighting, sunlight, and the types and intensity of other colours in the surroundings. Storage, transport and application conditions, as well as the final result, are beyond our control and therefore cannot constitute a warranty in the legal sense. In all cases, statutory provisions and any third-party rights must be observed.



WARRANTY:

Cameleo Leśniewicz Gratkowska Spółka Jawna warrants that Cameleo products are of merchantable quality in accordance with the standards declared by Cameleo. Cameleo products are covered by the warranty provided that they are used in accordance with the instructions in the Product Technical Data Sheets and Decorative Effect Technical Data Sheets. Products are not covered by the warranty if they are not used in accordance with the information in the Product Technical Data Sheets and Decorative Effect Technical Data Sheets. Liability under this warranty (if the product proves defective) is strictly limited to replacement of the product or a refund of its purchase price. This warranty is valid for one year from the date of purchase of the product.

MANUFACTURER:

CAMELEO Leśniewicz Gratkowska Spółka Jawna, ul. Sikorskiego 139, 63-100 Psarskie. Tel. 61-28-35-899

